

## CAP-I-62386

### USB Interface for DALI Networks



#### General

Dimensions (W × H × D)	85 mm × 21 mm × 12.4 mm (without cable)
Weight	50 g (without cable)
Degree of protection	IP 30

#### Voltage supply

Via computer	Via USB port
Via DALI device	Maximum 22.5 V (230 VAC tolerant)

#### Connectors and Interfaces

Plug-in connector for connecting to a computer	USB 2.0 Type A
Plug-in connector for connecting to a DALI device	Prepared for mounting a connector
Plug-in connector for mounting in a control cabinet	Prepared for mounting a connector

#### Connection cables

Type	2 × 0,25 mm <sup>2</sup> LIYCY
Length	2.50 m (re-assembled)

#### Climatic environmental conditions

Operating temperature range	-40 °C to +60 °C
Storing and transport temperature range	-40 °C to +85 °C
Maximum humidity	0 % to 90 % (non-condensing)

#### Standards, Guidelines and Approvals

CE	Conformity marking
EN 60664	Insulation coordination
EN 61000-6-2, EN 61000-6-3, EN 61547	EMC
DIN EN 62386-101	General requirements – DALI system components
DIN EN 62386-102	General requirements – DALI control gears
DIN EN 62386-103	General requirements – DALI control devices

#### Item number

CAP-I-62386	946-1-02-01-01
USB Interface for DALI Networks	

#### Related products with item number

CAP-62386	946-1-01-00-01
Protocol Analyzer for DALI Networks	